

## SUPER PROFESSIONAL HD 52X52 - 52X76

### GENERAL FEATURES




Aluminium 6082-T6 alloy Truss, main tube Ø 50 x 4 mm, diagonal tube Ø 30 x 3 mm.

### 52X52 TRUSS

It can contain SuperProfessional 35, Professional 30 and 40, Euro 29, SuperLite 25, Elite 25 and 30, and Standard linear trusses.


### COUPLING SYSTEM

Coupling system, accessories and purposes are the same as Superprofessional 35.



TA 4003  
"R" clip 3mm

TB 1000  
SuperProfessional  
coupling Set



TA 1001  
Quick pin for  
SuperProfessional spigot

TRUSS LENGTH	52x52 CODE	52x52 WEIGHT	52x76 CODE	52x76 WEIGHT
1,0 m	TB 1510	19,50 kg	TB 1710	30,10 kg
2,0 m	TB 1520	29,60 kg	TB 1720	38,70 kg
3,0 m	TB 1530	40,20 kg	TB 1730	49,70 kg

LOADING FIGURES

TRUSS LENGTH	52x52		52x76	
	▲	▲▲▲▲	▲	▲▲▲▲
8 m	1976	494	2500	500
10 m	1554	311	2432	486
12 m	1267	211	1998	333
14 m	1058	151	1683	240
16 m	898	112	1442	180
18 m	770	86	1252	139
20 m	664	66	1096	110
22 m	575	52	966	88
24 m	499	42	855	71
26 m	431	33	758	58

